

Epegrip



Surface
grinding

CONSTRUCTION

- + Solid body with a low height
- + Clamping surface with a true transverse pole division, steel/epoxy resin 14/8 mm
- + Nominal holding force: 120 N/cm²

APPLICATION

- + General purpose finish grinding
- + Minimum workpiece thickness: 6 mm
- + Minimum workpiece length: 40 mm



| Model | W [mm] | L [mm] | H [mm] | Weight [kg] |
|-------------|-----------|-----------|-----------|----------------|
| EPEG200400 | 200 | 400 | 79 | 39 |
| EPEG250500 | 250 | 500 | 79 | 61 |
| EPEG300600 | 300 | 600 | 79 | 89 |
| EPEG400800 | 400 | 800 | 79 | 155 |
| EPEG3001000 | 300 | 1000 | 82 | 151 |
| EPEG5001000 | 500 | 1000 | 82 | 252 |
| EPEG6001000 | 600 | 1000 | 82 | 309 |

SCOPE OF SUPPLY

- + Back and end stop
- + Set of clamps
- + Power cord of 3 m
- + Sizes 300 x 600 mm and bigger have studs for handling

SUITABLE CONTROL UNIT

- + Consult with us a suitable control unit and electrical connection.
- + For more information, refer to the section **control units on pg. 33.**

